


## AI-HT-T9



### Thermometry Mobile Computer



AI-HT-T9 is a high-performance intelligent handheld terminal which designed for temperature measurement. It is developed based on Android system, with high-performance processor, first-class configuration and fast operation, this device can be widely used in multiple temperature measurement scenarios. Temperature measurement module on top is more convenient for the user to operate, and helps the user to quickly realize information management and improve work efficiency.



## Specification

### Performance

<b>CPU</b>	Cortex-A53 Octa-core 2.5GHz
<b>RAM+ROM</b>	3GB + 32GB
<b>Expansion</b>	Supports up to 128 GB Micro SD card
<b>Operating System</b>	Android 8.1; Soti MobiControl, SafeUEM supported

### Communication

<b>WLAN</b>	IEEE802.11 a/b/g/n/ac, 2.4G/5G dual-band, internal antenna
	2G: 900/1800 MHz
	3G: WCDMA: B1/B8
<b>WWAN (China)</b>	CDMA2000 EVDO: BC0
	TD-SCDMA: B34/B39
	4G: B1/B3/B5/B8/B34/B38/B39/B40/B41
<b>WWAN (Europe)</b>	2G: 850/900/1800/1900 MHz
	3G: B1/B2/B4/B5/B8
	4G: B1/B3/B5/B7/B8/B20/B40
<b>WWAN(America)</b>	2G: 850/900/1800/1900 MHz
	3G: B1/B2/B4/B5/B8
	4G: B2/B4/B7/B12/B17/B25/B66
<b>WWAN (Others)</b>	Depending on the country's ISP
<b>Bluetooth</b>	Bluetooth v2.1+EDR,3.0+HS,v4.1+HS
<b>GNSS</b>	GPS/AGPS, GLONASS, BeiDou; internal antenna

### Physical Characteristics

<b>Dimensions</b>	163.8 * 79.2 * 13.8 mm / 6.45 * 3.12 * 0.54 in
<b>Weight</b>	<242g / 8.5oz.
<b>Display</b>	5.2" IPS FHD 1920 x 1080
<b>Touch Panel</b>	Corning Gorilla Glass, multi-touch panel, gloves and wet hands supported
<b>Expansion Slot</b>	1 slot for SIM card, 1 slot for SIM or TF card
<b>Interfaces</b>	USB2.0 Type-C, OTG, supports TypeC headphones
<b>Audio</b>	Speaker, 2 microphones
<b>Keypad</b>	4 front keys, 1 power key, 2 scan keys, 1 multifunctional key
	Main battery: Li-ion, rechargeable, 4000mAh
	Standby: over 300 hours
<b>Power</b>	Continuous use: over 12 hours (depending on user environment)
	Charging time: 2-3 hours (with standard adaptor and USB cable)
<b>Sensors</b>	Gravity sensor, Light Sensor, Proximity sensor, Vibration motor

### Developing Environment

<b>SDK</b>	Software Development Kit
<b>Language</b>	Java
<b>Tool</b>	Eclipse / Android Studio

### User Environment

<b>Operating Temp.</b>	-4°F to 122°F / -20°C to 50°C
<b>Storage Temp.</b>	-40°F to 158°F / -40°C to 70°C
<b>Humidity</b>	5%RH - 95%RH non condensing
<b>Drop Specification</b>	Multiple 1.8m / 5.9ft drops (at least 20 times) to the concrete across the operating temperature range
<b>Tumble Specification</b>	1000 x 0.5m/1.6ft falls at room temperature
<b>Sealing</b>	IP65/IP67 per IEC sealing specifications
<b>ESD</b>	±15KV air discharge, ±6KV conductive discharge

### Data Collection

#### Temperature Collection

<b>Measure Position</b>	Human forehead / Object surface
<b>Measure Method</b>	Non-contact / Infrared
<b>Measure Distance</b>	1 - 3 cm
<b>Measure Range</b>	Human forehead: 32°C to 42.9°C; Object surface: -40°C to 115°C;
<b>Measure Accuracy</b>	Human forehead: ±0.2°C; Object surface: ±0.5°C;
<b>Measure Duration</b>	≤1S
<b>Spectral Range</b>	5.5 -15 μm
<b>Resolution</b>	0.02°C

\*The infrared module has 80 degrees limitation, the best measure angle should be in this range.

#### Camera

<b>Rear Camera</b>	13MP Autofocus with flash
<b>Front Camera (optional)</b>	5MP camera

#### NFC

<b>Frequency</b>	13.56MHz
<b>Protocol</b>	ISO14443A/B, ISO15693, NFC-IP1, NFC-IP2, etc.
<b>Chips</b>	M1 card (S50, S70), CPU card, NFC tags, etc.
<b>Range</b>	2-4cm

#### Barcode Scanning (Optional)

<b>2D Imager Scanner</b>	Zebra SE4710/Honeywell N6603
<b>1D Symbolologies</b>	UPC/EAN, Code128, Code39, Code93, Code11, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Chinese 2 of 5, MSI, RSS, etc.
<b>2D Symbolologies</b>	PDF417, MicroPDF417, Composite, RSS, TLC-39, Datamatrix, QR code, Micro QR code, Aztec, MaxiCode; Postal Codes: US PostNet, US Planet, UK Postal, Australian Postal, Japan Postal, Dutch Postal (KIX), etc.

#### Iris (optional)

<b>Rate</b>	<150ms
<b>Range</b>	20-40cm
<b>FAR</b>	1/10000000
<b>Protocol</b>	ISO/IEC 19794-6, GB/T 20979-2007

\*Iris is alternative to front camera.

## Accessories(See details in Accessory Guide)



AC Adaptor



USB Cable



Sim Tray Ejector



Lanyard



Cradle (Optional)



Holster(Optional)